



EFB500 5A-800A 500V AC/DC

- Class of Operation: aR aBAT
- Standard: IEC60269.GB13539
- Breaking Capacity: AC100kA,DC50kA
- Time Constant: ≤15ms



EFB750 5-800A 750V AC/DC

- Class of Operation: aR aBAT
- Standard: IEC60269.GB13539
- Breaking Capacity: AC100kA,DC50kA
- Time Constant: ≤15ms



EFB1000 5A-800A 1000V AC/DC

- Class of Operation: aR aBAT
- Standard: IEC60269.GB13539
- Breaking Capacity: AC100kA,DC50kA
- Time Constant: ≤15ms

Model	Rated current	Overall dimension/size								
		A	B	C	D	E	F	G	ΦH	
EFB500-2	5A-100A	92	77	68	53	18	3.2	9	24	
EFB500-3	125A- 200A	99	84	70	53	26	5	9	31	
EFB500-4	225A-400A	115	93	76	53	26	6	10.5	37	
EFB500-5	450A- 600A	109	87	70	53	38	6	10.5	49	
EFB500-6	700A- 800A	148	117	85	53	51	10	13.5	62	

Model	Rated current	Overall dimension/size								
		A	B	C	D	E	F	G	ΦH	
EFB750-2	5A-80A	112	97	83	66	18	3.2	9	24	
EFB750-3	90A- 160A	112	97	83	66	26	5	9	31	
EFB750-4	175A-350A	134	112	95	72	26	6	10.5	37	
EFB750-5	375A- 500A	128	106	89	72	38	6	10.5	49	
EFB750-6	600A- 800A	167	136	103	72	51	10	13.5	62	

Model	Rated current	Overall dimension/size								
		A	B	C	D	E	F	G	ΦH	
EFB1000-2	5A-80A	124	109	95	78	18	3.2	9	24	
EFB1000-3	90A- 160A	124	109	95	78	26	5	9	31	
EFB1000-4	175A-315 A	144	122	105	82	26	6	10.5	37	
EFB1000-5	350A- 500A	144	122	105	88	38	6	10.5	49	
EFB1000-6	600A- 800A	183	152	119	88	51	10	13.5	62	

