




EHJ800A

EHJ800A

Basic Technical Parameters (at normal conditions)

Electric Parameters			
Contact type	SPST-NO	Instantaneous maxi (closing) current	3200A, ≤1s
Rated voltage of contacts (DC)	≤48V	Insulation resistance(MΩ)	≥100
Rated current of contacts (A)	800	Dielectric withstand voltage	1500V,p.f. 1min, no breakdown
Voltage drop on contacts(mV)	≤80 (at 100A)	Electric cycles (10 <sup>4</sup> )	≥2
Coil voltage specification(DC)	24V, 48V etc	Mechanical cycles (10 <sup>4</sup> )	≥30
DC power consumption of coil (W)	Start ≤ 275, keep ≤ 8.5	Temperature rise on outgoing terminal	≤65
Pickup voltage(DC)	≤70%Us	Temperature rise of coil(K)	≤85
Release voltage(DC)	≥5%Us; ≤40%Us	Insulation grade of enameled wire	Class B (130°C)
Pickup time(ms)	≤30	Material of contact	AgCuO(10)/Cu
Release time(ms)	≤50	Working duty	Continuous operating duty
Mechanical/Ambient Conditions			
Torque of outgoing terminal on contact M12(N.m)	≥35.0N appropriate	Protection grade	IP50
Torque of outgoing terminal on coil M4(N.m)	≥1.2N appropriate	Mounting methods	Freely
Working temperature	(-25~+55)°C	Vibration	Sine shock: 2.5g, (5~50) Hz
Mounting altitude	≤2Km	Impact	50g, 11ms(Half sine)

Outline and Mounting Picture




Application

The products are mainly used to control switching on/off of power supply of storage battery car, electric forklift, electric winch, electric car, excavator, air conditioner in vehicle, power source for communication facility.

Ordering Notice

For example: EHJ800A/24V  
The DC contactor of main contact is one NO, rated voltage not more than DC 80V, current 800A, coil voltage is DC12V

Model and Meanings



Electric Wiring Diagram

